

The logo for Total Fire Fire Extinguisher. It features a red flame icon to the left of the word "total" in grey and "fire" in red. Below this, the words "FIRE EXTINGUISHER" are written in white capital letters.

totalfire
FIRE EXTINGUISHER



wow w.totalfire.co.id



 **totalfire**
FIRE EXTINGUISHER



MODEL	DRY CHEMICAL POWDER ABC 90 PREMIUM						
TYPE	*STORE PRESSURE N2 (NITROGEN)						
MODEL	P 100	P 200	P 300	P 450	P 600	P 900	P 1200
CAPACITY	1 KG	2 KG	3 KG	4.5 KG	6 KG	9 KG	12 KG
CLASS FIRE	A, B, C						
TUBE CYLINDER	WITHOUT LAS						
TIME SPRAY (Seconds)	8	10	11	13	16	20	25
EFFECTIVE BLACKOUT (Seconds)	2	2	3	4	5	2	8
DISTANCE SPRAY (m)	2 until 5	2 until 5	2 until7	3 until 9	3 until 9	3 until 9	3 until 9
TALL (mm)	300	374	460	455	540	575	665
WIDE (incl hose) mm	130	145	280	285	300	310	320
DIAMETER TUBE (mm)	90	130	130	160	160	190	190
TEMPERATURE (°C)	-20 until 60						
TEST PRESS TUBE	25 Bar						
PRESSURE IN TUBE	15 Bar						
HEAVY TOTAL (Kg)	2	3.8	5.4	7.2	9.3	13.1	16.4
FIRE RATING (Labs. Service PMK)	2A. 10B	3A. 20B	4A. 30B	6A. 40B	7A. 60B	12A. 80B	12A. 80B
FINISHING (Paint)	RED POWDER COATINGS						



Totalfier FK5112 is a fire extinguisher clean, effective and does not leave marks, FK5112 as a substitute for Halon 1211 is effective for all types of class A BC fires and safe for electronic equipment (non-conductive).

Totalfier AFFF-FOAM is ver effective in extinguishing class A and B fires. Totalfier AFF-FOAM 6%formulation used by Totalfier fire extinguishers has a very high ability to deal with fires caused by fuel oil and flammable liquids through the Foam Extreme layer that covers the entire oil pool area

Totalfire CO2 is a clean, safe and highly capable fire extinguisher to extinguish class B and C fires caused by electrical equipment. The portable unit uses a lightweight, rust-resistant aluminium cylinder tube and is equipped with a non-conductive anti-static funnel.



	FK-5112				FOAM AFF 3%M AFF 3%		CARBON DIOXIDEARBON		
TYPE	*STORE PRESSURE ARGON				*STORE PRESSURE N2 (NITROGEN)		OWN PRESSURE		
MODEL	FE-500-T	FE 150	FE 350	FE 500	F 600	F 900	C 200	C 500	C 680
CAPACITY	5KG/12.5m ³	1.5 KG	3.5 KG	5 KG	6 Ltr	9 Ltr	2 KG	5 KG	6.8 KG
CLASS FIRE	A, B, C				A, B		B, C		
TUBE CYLINDER	LAS	WITHOUT LAS							
TIME SPRAY (Seconds)	10	8	10	13	13	18	9	20	25
EFFECTIVE blackout (Seconds)		6	8	12	23	25	2	3	4
DISTANCE SPRAY (m)		3 until 6	4 until 8	4 until 12	4 until 8	4 until 8	2 until 3	2 until 3	2 until 3
TALL (mm)	380	345	450	565	540	575	520	830	1025
WIDE (incl hose) mm		135	280	300	300	310	250	380	380
DIAMETER TUBE (mm)	210	84	130	160	160	190	114	152	152
TEMPERATURE (°C)	-20 until 60				1 until 65		-20 until 60		
TEST PRESS TUBE	25 Bar					250 Bar			
PRESSURE IN TUBE	15 Bar					70 Bar			
HEAVY TOTAL (Kg)	7	2.9	6.6	9,5	9.5	13.2	7.6	17	22
FIRE RATING (Labs. Service PMK)					3A. 10B	5A. 12B	2B	6B	8B
FINISHING (Paint)	RED OUTDOORS POWDER COATINGS UV RESISTANCE								

TROLLEY

(WHEELED EXTINGUISHER)

FIRE EXTINGUISHER

MEDIA	FOAM AFFF 3%			CARBON DIOXIDE			DRY CHEMICAL POWDER ABC 90 PREMIUM			
TYPE	*STORE PRESSURE N2 (NITROGEN)			OWN PRESSURE			*STORE PRESSURE N2 (NITROGEN)			
MODEL	F 3000	F 5000	F 9000	C 900	C 2300	C 4500	P 2000	P 2500	P 5000	P 6800
CAPACITY	30 Ltr	50 Ltr	90 Ltr	9 KG	23 KG	45 KG	20 KG	25 KG	50 KG	68 KG
CLASS FIRE	A, B			B, C			B, C			
TUBE CYLINDER	LAS			STEEL			LAS			
TIME SPRAY (Seconds)	40	55	120	30	50	60	30	30	50	60
EFFECTIVE blackout (Seconds)	35	51	59	5	11	20	18	19	41	61
DISTANCE SPRAY (m)	6 until 9			2 until 3			4 until 10			
TALL (mm)	940	1100	1350	1200	1500	1600	940	940	1100	1100
WIDE (incl hose) mm	576			460	526	576	576			
DIAMETER TUBE (mm)	370			152	220	268	370			
TEMPERATURE (°C)	1 until 65			-20 until 60						
TEST PRESS TUBE	31 Bar			250 Bar			31 Bar			
PRESSURE IN TUBE	15 Bar			70 Bar			15 Bar			
HEAVY TOTAL (Kg)	75	100	140	50	95	136	65	70	100	118
FIRE RATING (Labs. Service PMK)	10A.80B	12A.125B	30A.125B	8B	8B	10B	20A.100B	20A.100B	30A.125B	30A.125B
FINISHING (Paint)	RED POWDER COATINGS									

Distributed by :

PT TOTALFIRE INDONESIA

THE PROMINENCE ALAM SUTERA

BLOK 38E NO. 49, SERPONG - TANGERANG SELATAN

P : 021 - 30052533

F : 021 - 30052532

E : info@totalfire.co.id